




BIRLA WHITE TILESTIX

Finish mast.
Pakad Zabardast.



 **ADITYA BIRLA**
BUILDING SOLUTIONS


Birla White

TILESTIX

WHITE CEMENT BASED PREMIUM TILE ADHESIVE


INTERIO


TX1




TILE ADHESIVE FOR INTERIOR WALL AND FLOOR


FOR CERAMIC TILES FIXING ON WALL AND FLOOR
HIGHER BOND STRENGTH AND FLEXIBILITY
ALTERNATIVE FOR OTHER BASE TILE ADHESIVES


 MIX ON SITE


 TOKEN INSIDE

20 kg
NET QUANTITY

 MIXABLE

 HIGHER ADHESION

 EASE OF USE

 BETTER OPEN TIME

TILESTIX INTERO

It is a polymer modified, White Cement-based thin-set tile adhesive for fixing high porosity tiles like ceramic/clay tiles, terracotta and small format natural stones.



DURABLE



HIGHER ADHESION



EASE OF USE



BETTER OPEN TIME



Features and Advantages:

- Can be used in internal areas, for floor applications.
- Water resistant - suitable for wet areas.
- Self-curing properties, which allows hassle-free application with minimum labor.
- Low VOC for healthy living.

Suitable for:

Horizontal surfaces over the cementitious substrate for indoor application in dry and wet areas.

Packaging: 20 kg bag

Technical Specifications:

Pot Life	Tensile Adhesion	Shear Adhesion	**Coverage	IS 15477: 2019	*Shelf life
2hrs.	> 0.7 N/mm ²	> 1.10 N/mm ²	Approx. 55-60 ft ²	Type 1'T'	12 months

* For sealed pack when stored under cover, out of direct sunlight, damp-proof condition and protect from extremes of temperature.

** Coverage will vary depending on trowel notch size, type and size of tile and substrate smoothness and evenness. For 20 kg bag at 3 mm thickness using 6 mm x 6 mm square notched trowel.

Application Areas:

Interior Floors	
Ceramic Tiles	✓
Semi Vitreous	✓
Tile On Tile	
Vitrified Tiles	
Porcelain Tiles	
Glass Mosaics	
Natural Stones - Granite/Marble	
Small Format Tiles	✓
Medium Format Tiles	
Large Format Tiles	

Properties As Per IS 15477: 2019

Variant	Intero	
Conforms to:	1T	
Testing Properties	Requirement	Test Results
1.Tensile Adhesion Strength		
a) Dry Condition, N/mm ²	Minimum 0.5	>0.7
b) Wet Condition, N/mm ²		
2.Shear Adhesion Strength		
a) Dry Condition, N/mm ²	Minimum 1.0	>1.10
b) Wet Condition, N/mm ²		
3.Slip Resistance, mm	≤ 0.5	<0.4

Physical Properties @ 25°C

Variant	Intero
Mixing Ratio by weight	0.24 – 0.26
Mixed Density, kg/liter	1.65 – 1.85
Open Time, minutes (IS 15477: 2019)	Approx. 20
Adjustability, minutes (IS 15477: 2019)	Approx. 20
Pot Life, hours	2
Setting Time, hours	24
Time to Heavy Traffic, hours	24
Adhesive Thickness, mm	3 - 12
Application Temperature (Substrate and Materials), °C	5 - 35



BIRLA WHITE TILESTIX RANGE



Use Birla White Tilelynk for excellent results.



Scan to
Know More

Birla White - A Unit of UltraTech Cement Limited,

9th Floor, Birla Centurion, Pandurang Budhkar Marg,
Worli, Mumbai - 400030

🌐 Website: www.birlawhite.com | 📞 Toll Free No.: 1800 11 1717

📘 www.facebook.com/BirlaWhiteCement | 🐦 twitter.com/BirlaWhite

✉ bw-consumercare@adityabirla.com